

Twill Jean Wipes

100% woven cotton wipe in a twill construction

The Twill Jean Wipe is a 100% cotton fabric, woven in a 2 x 1 twill construction. The Twill Jean Wipe is very absorbent and has high thermal stability for high temperature applications. The edges are bias cut to prevent unraveling.



Excellent for surface cleaning or spill pick up.

These wipes meet the requirements of USP<797> and IEST-CC-RP004.4 for “non-shedding, low-lint, lint-free wipes”.



Features	Benefits
Strong and absorbent	<ul style="list-style-type: none"> • Suitable for high temperature applications
Bias cut edges	<ul style="list-style-type: none"> • Reduce unraveling
Sorbent wipe	<ul style="list-style-type: none"> • Suitable for surface cleaning or spill pick up

Part No.	Description	Size	Packaging
TJ-99S	Twill Jean Wipes Flat stacked	9" x 9" (230 x 230 mm)	300/bag; 6 bags/case
TJ-1212S	Twill Jean Wipes Flat stacked	12" x 12" (305 x 305 mm)	150/bag; 5 bags/case
TJ-1717S	Twill Jean Wipes Bulk	17" x 17" (432 x 432 mm)	75/bag; 6 bags/case

Product Information	
Material	100% cotton
Construction	Twill
Packaging materials	Outer bags (OB1, OB2), low density polyethylene (LDPE)  Case (CS), corrugated fiberboard (PAP) 



Technical Data		
Attribute (units)	Typical Value	Test Method
Basis weight, nominal; (g/m ²)	190	Contec Method
Sorbent capacity; (mL/m ²)	300	IEST-RP-CC004.4, Sec. 9.1
Sorptive rate; (seconds)	1.5	IEST-RP-CC004.4, Sec. 9.2
Non-volatile residue, NVR		IEST-RP-CC004.4, Sec. 8.1.1
In deionized water; (g/m ²)	0.405	
In isopropyl alcohol; (g/m ²)	0.151	
Specific ions		IEST-RP-CC004.4, Sec. 8.2.2
Sodium; (ppm)	105	
Chloride; (ppm)	10	
Particles, readily releasable		
Particles ≥ 0.5µm; (x10 ⁶ /m ²)	80	IEST-RP-CC004.2, Sec. 5.1
Fibers ≥ 100µm; (x 10 ³ /m ²)	98	IEST-RP-CC004.2, Sec. 5.2

Recycle Symbols

PET	
HDPE	
LDPE	
PP	
PAP	

Packaging	EA/OB1	OB1/OB2	OB2/CS	EA/CS
TJ-99S	300	1	6	1,800
TJ-1212S	150	1	5	750
TJ-1717S	75	1	6	450

EA = each; OB = outer bag; CS = case

Notes

- a) The data shown are typical values and should not be used as product specifications.
- b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods:

- 1. CTM = Contec Test Method
- 2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of Environmental Sciences and Technology, Rolling Meadows IL