

# Twill Jean Wipes

## 100% woven cotton wipe in a twill construction

The Twill Jean Wipe is a 100% cotton fabric, woven in a 2 x 1 twill construction. The Twill Jean Wipe is very absorbent and has high thermal stability for high temperature applications. The edges are bias cut to prevent unraveling.

Excellent for surface cleaning or spill pick up.



Features	Benefits
Strong and absorbent	• Suitable for high temperature applications
Bias cut edges	• Reduce unraveling
Sorbent wipe	• Suitable for surface cleaning or spill pick up

Part No.	Description	Size	Packaging
TJ-99	Twill Jean Wipes Flat stacked	230 x 230 mm	300 per bag / 12 bags per case
TJ-1212	Twill Jean Wipes Flat stacked	305 x 305 mm	150 per bag / 10 bags per case
TJ-1717	Twill Jean Wipes Bulk	432 x 432 mm	75 per bag / 12 bags per case

Product Information	
Material	100% cotton
Reticulation method	Twill





Technical Data		
Attribute (units)	Typical Value	Test Method
Basis weight, nominal; (g/m²)	190	Contec Method
Sorbent capacity; (mL/m²)	300	IEST-RP-CC004.3, Sec. 8.1
Sorptive rate; (seconds)	1.5	IEST-RP-CC004.3, Sec. 8.2
Non-volatile residue, NVR		IEST-RP-CC004.3, Sec. 7.1.2
In deionized water; (g/m²)	0.405	
In isopropyl alcohol; (g/m²)	0.151	
Specific ions		IEST-RP-CC004.3, Sec. 7.2.2
Sodium; (ppm)	105	
Chloride; (ppm)	10	
Particles, readily releasable		
Particles ≥ 0.5µm; (x10⁶/m²)	80	IEST-RP-CC004.2, Sec. 5.1
Fibres ≥ 100µm; (x 10³/m²)	98	IEST-RP-CC004.2, Sec. 5.2

- Notes**
- a) The data shown are typical values and should not be used as product specifications.
  - b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
  - c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

- Test Methods**
- 1. CTM = Contec Test Method
  - 2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL.

Packaging

Packaging Materials				
Outer bags	Low density polyethylene (LDPE) 			
Case	Corrugated fibreboard (PAP) 			
Packaging Configuration	EA/OB1	OB1/OB2	OB2/CS	EA/CS
TJ-99	300	1	12	3,600
TJ-1212	150	1	10	1,500
TJ-1717	75	1	12	900

EA = Each; OB1 = Outer Bag 1; OB2 = Outer Bag 2; CS = Case

Recycle Key	
PET	
LDPE	
PAP	

For more information or to request a sample,  
email [infoeu@contecinc.com](mailto:infoeu@contecinc.com) or phone +33 (0) 2 97 43 76 98.